



Commercial & Industrial Door Air Curtain | Dual-Speed Copper Motor

TECHNICAL SPECIFICATIONS

PARAMETER	SPECIFICATION
Motor	0.20 HP, 220 V, dual-speed copper motor, 2800 RPM
Air Velocity	High: up to 21 m/sec Low: 18 m/sec
Blower	PVC (virgin), 5" (D) × 5" (H), centrifugal type
Blower Housing	GI sheet
Noise Level	70 dB (Low) – 85 dB (High)
Body	Heavy MS body with powder coating; available in SS body
Installation Height	Suitable for doors up to 8 ft height

APPLICATION / BENEFITS

- 01** Helps protect the entrance from dust and insects
- 02** Helps maintain a cool and hygienic environment

MODEL SELECTION

MODEL NO.	DIMENSION (mm)	NO. OF BLOWERS	NO. OF MOTORS
TAC3	915 × 220 × 245	3	2
TAC3.5	1067 × 220 × 245	3	2
TAC4	1220 × 220 × 245	4	2
TAC5	1524 × 220 × 245	5	3
TAC6	1830 × 220 × 245	6	3
TAC7	2134 × 220 × 245	7	4
TAC8	2438 × 220 × 245	8	4

www.trapenex.com

Technical data as provided in the supplied specification sheet.